



OP-185


Metal Openframe Touch Screen Display
Low Consumption Power
Contrast Increase

❖ Specification


LCD Type	18.5" Active Matrix , TFT
Aspect Ratio	16:9 Format
Resolution	1366x768(HD)
Pixel Pitch	0.3mm x 0.3mm
Active Area	409.8 x 230.4 mm
Contrast Ratio	1000:1 (typ.)
Brightness	250 (cd/m ²)
View Angle (H/V)	170 / 160
Response Time	5ms. (typ.)
Backlight Type	LED Backlight
Input Signal	VGA / DVI-D (option)
Plug & Play (pnp.)	VESA DDC 2B
Display Control	Display On / Off , Adjustment , OSD Control
Power Input	DC 12 V Adapter
Power Consumption	13.6 watt (Max) < 1watt (Stand By Mode)
Operation Temperature	0° to 50°
Operation Humidity	80% (max)
Frame / VESA Mount	VESA 100 x 100
Weight	N.W kgs / G.W kgs
Dimension	420.2 x 258.9 x 43




❖ Dimension



FRONT VIEW



REAR VIEW



❖ Ordering Information

OP-185	18.5" Openframe Only
OPT-185R	18.5" Openframe + 5-W Resistive Touchscreen
OPT-185C	18.5" Openframe + Capacitive Touchscreen

❖ Accessories

12V DC Adapter , Power Cord , VGA Cable , USB Cable , Touch Driver